

2011 (平成 23 )年度      ネポンハウスカオンキ   熱効率および燃料消費量 経年変化一覧表

【目次】

・ HK-0型, 1型, 3型	1 ㏆-ジ
・ HK-4型, 5型, 6型	2 ㏆-ジ
・ HK-8型, 10型	3 ㏆-ジ
・ HK-11型, 15型, 20型	4 ㏆-ジ
・ HK-17型, 22型	5 ㏆-ジ
<hr/>	
・ HK-23型	6 ㏆-ジ
・ HK-25型, 25E型	7 ㏆-ジ
・ HK-25Z型	8 ㏆-ジ
・ HK-26型, 26Z型, 26V型 (現行)	9 ㏆-ジ
・ HK-24型	10 ㏆-ジ
<hr/>	
・ HK-24Z型	11 ㏆-ジ
・ HK-24V型 (現行)	12 ㏆-ジ
・ HK-27型	13 ㏆-ジ
・ HK-27Z型	14 ㏆-ジ
・ HK-27V型 (現行)	15 ㏆-ジ

2011年 4月  
ネポン株式会社

ネポン株式会社

【ハウスカンキ 0.1.3型シリーズ】1/2

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量																		
				(kcal/h)	(kW)					1965		1966		1967		1968		1969		1970		1971						
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)					
O型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A重油	2.3~5.0	69.9%	5.2	70.1%	5.2	70.4%	5.2	70.6%	5.2	70.8%	5.2	71.0%	5.1	71.2%	5.1					
			HK150SE	32,000	37.2	4.6	80%	A重油	2.3~5.0	69.9%	5.2	70.1%	5.2	70.4%	5.2	70.6%	5.2	70.8%	5.2	71.0%	5.1	71.2%	5.1					
			HK300TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1	70.8%	12.1	71.0%	12.0	71.2%	12.0					
			HK300TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1	70.8%	12.1	71.0%	12.0	71.2%	12.0					
			HK300SE	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1	70.8%	12.1	71.0%	12.0	71.2%	12.0					
			HK300SC	75,000	87.2	10.7	80%	A重油	6.6~9.9	69.9%	12.2	70.1%	12.2	70.4%	12.2	70.6%	12.1	70.8%	12.1	71.0%	12.0	71.2%	12.0					
			HK400TE	87,000	101	12.3	80%	A重油	9.9~13.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1	70.8%	14.0	71.0%	14.0	71.2%	13.9					
			HK400TC	87,000	101	12.3	80%	A重油	9.9~13.2	69.9%	14.2	70.1%	14.1	70.4%	14.1	70.6%	14.1	70.8%	14.0	71.0%	14.0	71.2%	13.9					
			HK500TC	125,000	145	17.8	80%	A重油	13.2~16.5	69.9%	20.4	70.1%	20.3	70.4%	20.3	70.6%	20.2	70.8%	20.1	71.0%	20.1	71.2%	20.0					
HK600TC	150,000	174	21.3	80%	A重油	16.5~19.8	69.9%	24.5	70.1%	24.4	70.4%	24.3	70.6%	24.2	70.8%	24.2	71.0%	24.1	71.2%	24.0								
1型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A重油	6.6~9.9														71.2%	12.0				
			HK301TC	75,000	87.2	10.7	80%	A重油	6.6~9.9															71.2%	12.0			
			HK401TE	87,000	101	12.3	80%	A重油	9.9~13.2																71.2%	13.9		
			HK401TC	87,000	101	12.3	80%	A重油	9.9~13.2																	71.2%	13.9	
			HK501TC	125,000	145	17.8	80%	A重油	13.2~16.5																		71.2%	20.0
			HK601TC	150,000	174	21.3	80%	A重油	16.5~19.8																			71.2%
現行機種 (機器熱効率 90%) へ更新した場合の 経年変化節減率 ※同等熱出力換算									22.3%	22.1%	21.8%	21.6%	21.3%	21.1%	20.9%													

【ハウスカンキ 0.1.3型シリーズ】2/2

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量															
				(kcal/h)	(kW)					1972		1973		1974		1975		1976		1977		1978			
										%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
O型	1965 (S40)	1976 (S51)	HK150TE	32,000	37.2	4.6	80%	A重油	2.3~5.0	71.5%	5.1	71.7%	5.1	71.9%	5.1	72.1%	5.1	72.3%	5.0						
			HK150SE	32,000	37.2	4.6	80%	A重油	2.3~5.0	71.5%	5.1	71.7%	5.1	71.9%	5.1	72.1%	5.1	72.3%	5.0						
			HK300TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	71.5%	12.0	71.7%	11.9	71.9%	11.9	72.1%	11.9	72.3%	11.8						
			HK300TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	71.5%	12.0	71.7%	11.9	71.9%	11.9	72.1%	11.9	72.3%	11.8						
			HK300SE	75,000	87.2	10.7	80%	A重油	6.6~9.9	71.5%	12.0	71.7%	11.9	71.9%	11.9	72.1%	11.9	72.3%	11.8						
			HK300SC	75,000	87.2	10.7	80%	A重油	6.6~9.9	71.5%	12.0	71.7%	11.9	71.9%	11.9	72.1%	11.9	72.3%	11.8						
			HK400TE	87,000	101	12.3	80%	A重油	9.9~13.2	71.5%	13.9	71.7%	13.8	71.9%	13.8	72.1%	13.8	72.3%	13.7						
			HK400TC	87,000	101	12.3	80%	A重油	9.9~13.2	71.5%	13.9	71.7%	13.8	71.9%	13.8	72.1%	13.8	72.3%	13.7						
			HK500TC	125,000	145	17.8	80%	A重油	13.2~16.5	71.5%	19.9	71.7%	19.9	71.9%	19.8	72.1%	19.8	72.3%	19.7						
HK600TC	150,000	174	21.3	80%	A重油	16.5~19.8	71.5%	23.9	71.7%	23.9	71.9%	23.8	72.1%	23.7	72.3%	23.6									
1型	1971 (S46)	1978 (S53)	HK301TE	75,000	87.2	10.7	80%	A重油	6.6~9.9	71.5%	12.0	71.7%	11.9	71.9%	11.9	72.1%	11.9	72.3%	11.8	72.5%	11.8	72.8%	11.7		
			HK301TC	75,000	87.2	10.7	80%	A重油	6.6~9.9	71.5%	12.0	71.7%	11.9	71.9%	11.9	72.1%	11.9	72.3%	11.8	72.5%	11.8	72.8%	11.7		
			HK401TE	87,000	101	12.3	80%	A重油	9.9~13.2	71.5%	13.9	71.7%	13.8	71.9%	13.8	72.1%	13.8	72.3%	13.7	72.5%	13.7	72.8%	13.6		
			HK401TC	87,000	101	12.3	80%	A重油	9.9~13.2	71.5%	13.9	71.7%	13.8	71.9%	13.8	72.1%	13.8	72.3%	13.7	72.5%	13.7	72.8%	13.6		
			HK501TC	125,000	145	17.8	80%	A重油	13.2~16.5	71.5%	19.9	71.7%	19.9	71.9%	19.8	72.1%	19.8	72.3%	19.7	72.5%	19.6	72.8%	19.6		
			HK601TC	150,000	174	21.3	80%	A重油	16.5~19.8	71.5%	23.9	71.7%	23.9	71.9%	23.8	72.1%	23.7	72.3%	23.6	72.5%	23.6	72.8%	23.5		
3型	1974 (S49)	1978 (S53)	HK303TE	75,000	87.2	10.7	80%	A重油	6.6~9.9					71.9%	11.9	72.1%	11.9	72.3%	11.8	72.5%	11.8	72.8%	11.7		
			HK303TC	75,000	87.2	10.7	80%	A重油	6.6~9.9					71.9%	11.9	72.1%	11.9	72.3%	11.8	72.5%	11.8	72.8%	11.7		
			HK403TE	87,000	101	12.3	80%	A重油	9.9~13.2					71.9%	13.8	72.1%	13.8	72.3%	13.7	72.5%	13.7	72.8%	13.6		
			HK403TC	87,000	101	12.3	80%	A重油	9.9~13.2					71.9%	13.8	72.1%	13.8	72.3%	13.7	72.5%	13.7	72.8%	13.6		
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算									20.6%	20.4%	20.1%	19.9%	19.6%	19.4%	19.1%										

ネボン株式会社

【ハウスコンキ 4.5.6型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量												
				(kcal/h)	(kW)						1978		1979		1980		1981		1982		1983		
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	
4型 ・ 5型	1978 (S53)	1981 (S56)	HK155SE	32,000	37.2	4.3	88.0%	A重油	3.3~4.95			80.8%	4.5	81.0%	4.5	81.2%	4.5	81.4%	4.5				
			HK155TE	32,000	37.2	4.3	88.0%	A重油	3.3~4.95			80.8%	4.5	81.0%	4.5	81.2%	4.5	81.4%	4.5				
			HK204TC	50,000	58.1	6.7	88.0%	A重油	4.95~6.6	低床タイプ		80.8%	7.1	81.0%	7.0	81.2%	7.0	81.4%	7.0				
			HK205TE	50,000	58.1	6.7	88.0%	A重油	4.95~6.6			80.8%	7.1	81.0%	7.0	81.2%	7.0	81.4%	7.0				
			HK205TC	50,000	58.1	6.7	88.0%	A重油	4.95~6.6			80.8%	7.1	81.0%	7.0	81.2%	7.0	81.4%	7.0				
			HK304TC	75,000	87.2	10.0	88.0%	A重油	6.6~9.9	低床タイプ		80.8%	10.6	81.0%	10.6	81.2%	10.5	81.4%	10.5				
			HK305SE	75,000	87.2	10.0	88.0%	A重油	6.6~9.9			80.8%	10.6	81.0%	10.6	81.2%	10.5	81.4%	10.5				
			HK305SC	75,000	87.2	10.0	88.0%	A重油	6.6~9.9			80.8%	10.6	81.0%	10.6	81.2%	10.5	81.4%	10.5				
			HK305TE	75,000	87.2	10.0	88.0%	A重油	6.6~9.9			80.8%	10.6	81.0%	10.6	81.2%	10.5	81.4%	10.5				
			HK305TC	75,000	87.2	10.0	88.0%	A重油	6.6~9.9			80.8%	10.6	81.0%	10.6	81.2%	10.5	81.4%	10.5				
			HK404TC	87,000	101	11.6	88.0%	A重油	9.9~13.2	低床タイプ		80.8%	12.3	81.0%	12.2	81.2%	12.2	81.4%	12.2				
			HK405TE	87,000	101	11.6	88.0%	A重油	9.9~13.2			80.8%	12.3	81.0%	12.2	81.2%	12.2	81.4%	12.2				
			HK405TC	87,000	101	11.6	88.0%	A重油	9.9~13.2			80.8%	12.3	81.0%	12.2	81.2%	12.2	81.4%	12.2				
			HK505TC	125,000	145	16.6	88.0%	A重油	13.2~16.5			80.8%	17.6	81.0%	17.6	81.2%	17.5	81.4%	17.5				
HK605TC	150,000	174	19.9	88.0%	A重油	16.5~19.8			80.8%	21.2	81.0%	21.1	81.2%	21.1	81.4%	21.0							
6型	1981 (S56)	1983 (S58)	HK156SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							81.4%	4.5	81.6%	4.5	81.9%	4.5		
			HK156TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95							81.4%	4.5	81.6%	4.5	81.9%	4.5		
			HK206TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6							81.4%	7.0	81.6%	7.0	81.9%	7.0		
			HK206TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6							81.4%	7.0	81.6%	7.0	81.9%	7.0		
			HK306SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9							81.4%	10.5	81.6%	10.5	81.9%	10.4		
			HK306SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9							81.4%	10.5	81.6%	10.5	81.9%	10.4		
			HK306TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9							81.4%	10.5	81.6%	10.5	81.9%	10.4		
			HK306TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9							81.4%	10.5	81.6%	10.5	81.9%	10.4		
			HK316TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	低床タイプ						81.4%	10.5	81.6%	10.5	81.9%	10.4		
			HK406TE	87,000	101	11.3	88.0%	A重油	9.9~13.2							81.4%	12.2	81.6%	12.1	81.9%	12.1		
			HK406TC	87,000	101	11.3	88.0%	A重油	9.9~13.2							81.4%	12.2	81.6%	12.1	81.9%	12.1		
			HK416TC	87,000	101	11.3	88.0%	A重油	9.9~13.2	低床タイプ						81.4%	12.2	81.6%	12.1	81.9%	12.1		
HK506TC	125,000	145	16.2	88.0%	A重油	13.2~16.5							81.4%	17.5	81.6%	17.5	81.9%	17.4					
HK606TC	150,000	174	19.4	88.0%	A重油	16.5~19.8							81.4%	21.0	81.6%	20.9	81.9%	20.9					
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											10.3%	10.0%	9.8%	9.5%	9.3%	9.0%							

ネボン株式会社  
【ハウスナー 8,10型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																		
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988								
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)							
8型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			81.9%	4.5	82.1%	4.4	82.3%	4.4												
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			81.9%	4.5	82.1%	4.4	82.3%	4.4												
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			81.9%	7.0	82.1%	6.9	82.3%	6.9												
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			81.9%	7.0	82.1%	6.9	82.3%	6.9												
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9~13.2			81.9%	12.1	82.1%	12.1	82.3%	12.1												
			HK408TC	87,000	101	11.3	88.0%	A重油	9.9~13.2			81.9%	12.1	82.1%	12.1	82.3%	12.1												
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9~13.2			81.9%	12.1	82.1%	12.1	82.3%	12.1												
			HK508TC	125,000	145	16.2	88.0%	A重油	13.2~16.5			81.9%	17.4	82.1%	17.4	82.3%	17.3												
			HK608TC	150,000	174	19.4	88.0%	A重油	16.5~19.8			81.9%	20.9	82.1%	20.8	82.3%	20.8												
			10型	1985 (S60)	1988 (S63)	HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95						82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4				
HK160SC	32,000	37.2				4.2	88.0%	A重油	3.3~4.95							82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TE	32,000	37.2				4.2	88.0%	A重油	3.3~4.95							82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TC	32,000	37.2				4.2	88.0%	A重油	3.3~4.95							82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TEP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95		静音形					82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TCP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95		静音形					82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK210SE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210SC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TEP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6		静音形					82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TCP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6		静音形					82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK310SE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310SC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TEP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		静音形					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TCP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		静音形					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TCM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムナ					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TEM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムナ					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TFM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムナ					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK410TE	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TC	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TEP	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TCP	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TCM	87,000	101				11.3	88.0%	A重油	9.9~13.2		システムナ					82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TEM	87,000	101				11.3	88.0%	A重油	9.9~13.2		システムナ					82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TFM	87,000	101				11.3	88.0%	A重油	9.9~13.2		システムナ					82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK510TC	125,000	145				16.2	88.0%	A重油	13.2~16.5							82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2						
HK510TEP	125,000	145				16.2	88.0%	A重油	13.2~16.5		静音形					82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2						
HK510TCM	125,000	145	16.2	88.0%	A重油	13.2~16.5		システムナ					82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2									
HK610TC	150,000	174	19.4	88.0%	A重油	16.5~19.8							82.3%	20.8	82.5%	20.7	82.7%	20.7	83.0%	20.6									
HK610TEP	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形					82.3%	20.8	82.5%	20.7	82.7%	20.7	83.0%	20.6									
HK610TCM	150,000	174	19.4	88.0%	A重油	16.5~19.8		システムナ					82.3%	20.8	82.5%	20.7	82.7%	20.7	83.0%	20.6									
HK810TC	200,000	233	25.9	88.0%	A重油	19.8~26.4							82.3%	27.7	82.5%	27.6	82.7%	27.6	83.0%	27.5									
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											9.0%	8.8%	8.6%	8.3%	8.1%	7.8%													

ネボ ン株式会社

【ハウスファンキ 11.15.20型シリーズ】

2011年度 (平成 23 年度) 熱効率率/燃料消費量 経年変化一覽表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																		
				(kcal/h)	(kW)						1987		1988		1989		1990		1991		1992		1993		1994		1995		
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	
11型・ 15型・ 20型	1987 (S62)	1995 (H7)	HK1520SC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		84.7%	5.1	85.0%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.1%	5.0	86.3%	5.0	86.5%	5.0	
			HK1520SE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		84.7%	5.1	85.0%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.1%	5.0	86.3%	5.0	86.5%	5.0	
			HK1520TC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		84.7%	5.1	85.0%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.1%	5.0	86.3%	5.0	86.5%	5.0	
			HK1520TE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		84.7%	5.1	85.0%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.1%	5.0	86.3%	5.0	86.5%	5.0	
			HK1520TGP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形		84.7%	5.1	85.0%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.1%	5.0	86.3%	5.0	86.5%	5.0
			HK1520TEP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形		84.7%	5.1	85.0%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.1%	5.0	86.3%	5.0	86.5%	5.0
			HK2020SC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6	
			HK2020SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6	
			HK2020TC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6	
			HK2020TE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6	
			HK2020TGP	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2020TEP	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2020TGS	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK2020TES	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形		84.7%	6.7	85.0%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.1%	6.6	86.3%	6.6	86.5%	6.6
			HK3015TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3015TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3020SC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3020SE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3020TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3020TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3020TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK3020TGP	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TEP	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TFP	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TGS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TES	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TFS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TGD	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	デラックス形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TED	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	デラックス形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3020TFD	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	デラックス形		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9
			HK3011TGE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		84.7%	10.1	85.0%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.1%	9.9	86.3%	9.9	86.5%	9.9	
			HK4015TC	87,000	101	11.0	90.0%	A重油	9.9~13.2		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5	
			HK4015TF	87,000	101	11.0	90.0%	A重油	9.9~13.2		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5	
			HK4020TC	87,000	101	11.0	90.0%	A重油	9.9~13.2		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5	
			HK4020TE	87,000	101	11.0	90.0%	A重油	9.9~13.2		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5	
			HK4020TF	87,000	101	11.0	90.0%	A重油	9.9~13.2		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5	
			HK4020TGP	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5
			HK4020TEP	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5
			HK4020TFP	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5
			HK4020TGS	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5
HK4020TES	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5			
HK4020TFS	87,000	101	11.0	90.0%	A重油	9.9~13.2	静音形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5			
HK4020TGD	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5			
HK4020TED	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5			
HK4020TFD	87,000	101	11.0	90.0%	A重油	9.9~13.2	デラックス形		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5			
HK4011TGE	87,000	101	11.0	90.0%	A重油	9.9~13.2		84.7%	11.7	85.0%	11.7	85.2%	11.6	85.4%	11.6	85.6%	11.6	85.8%	11.6	86.1%	11.5	86.3%	11.5	86.5%	11.5				
HK5015TC	125,000	145	15.8	90.0%	A重油	13.2~16.5		84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5				
HK5020TC	125,000	145	15.8	90.0%	A重油	13.2~16.5		84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.1%	16.6	86.3%	16.5	86.5%	16.5				
HK5020TGP	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形		84.7%	16.8	85.0%	16.8	85.2%	16.7	85.4%														

ネボン株式会社

【ハウスコンキ 17, 22型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						1995		1996		1997	
											%	(l/h)	%	(l/h)	%	(l/h)
17型 ・ 22型	1995 (H7)	1997 (H9)	HK1522SC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK1522SE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK1522TC	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK1522TE	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK1522TCP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形	86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK1522TEP	38,000	44.2	4.8	90.0%	A重油	3.3~4.95	静音形	86.5%	5.0	86.7%	5.0	86.9%	5.0
			HK2022SC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2022SE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2022TC	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2022TE	50,000	58.1	6.4	90.0%	A重油	4.95~6.0		86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2022TCS	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形	86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK2022TES	50,000	58.1	6.4	90.0%	A重油	4.95~6.0	静音形	86.5%	6.6	86.7%	6.6	86.9%	6.6
			HK3022SC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3022SE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3022TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3022TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3022TF	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3022TCS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3022TES	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3022TFS	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3017TC	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK3017TE	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		86.5%	9.9	86.7%	9.9	86.9%	9.8
			HK4022TC	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4022TE	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4022TF	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4022TCS	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4022TES	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4022TFS	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4017TC	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK4017TE	100,000	116	12.7	90.0%	A重油	9.9~13.2		86.5%	13.2	86.7%	13.1	86.9%	13.1
			HK5022TC	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
			HK5022TF	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4
HK5022TCS	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4			
HK5022TFS	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	86.5%	16.5	86.7%	16.4	86.9%	16.4			
HK5017TF	125,000	145	15.8	90.0%	A重油	13.2~16.5		86.5%	16.5	86.7%	16.4	86.9%	16.4			
HK6022TC	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6022TF	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6022TCS	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6022TFS	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK6017TF	150,000	174	19.0	90.0%	A重油	16.5~19.8		86.5%	19.8	86.7%	19.7	86.9%	19.7			
HK8022TF	200,000	233	19.0	90.0%	A重油	19.8~26.4		86.5%	26.4	86.7%	26.3	86.9%	26.2			
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											3.9%	3.7%	3.4%			

ネボン株式会社  
【ハウスオキ 23型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量											
				(kcal/h)	(kW)						2000		2001		2002		2003		2004		2005	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
23型	2000 (H12)	2005 (H17)	HK3023TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3023TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3023TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3023TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3023TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3023TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3023TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3023TRS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK4023TC	100,000	116	13.0	88.0%	A重油	9.9~13.2		85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4023TE	100,000	116	13.0	88.0%	A重油	9.9~13.2		85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4023TF	100,000	116	13.0	88.0%	A重油	9.9~13.2		85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4023TR	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4023TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4023TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4023TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4023TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2		85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK5023TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5023TE	125,000	145	16.2	88.0%	A重油	13.2~16.5		85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5023TF	125,000	145	16.2	88.0%	A重油	13.2~16.5		85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5023TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5023TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5023TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK6023TC	150,000	174	19.4	88.0%	A重油	16.5~19.8		85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8	86.5%	19.8	86.7%	19.7
			HK6023TE	150,000	174	19.4	88.0%	A重油	16.5~19.8		85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8	86.5%	19.8	86.7%	19.7
HK6023TF	150,000	174	19.4	88.0%	A重油	16.5~19.8		85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8	86.5%	19.8	86.7%	19.7			
HK6023TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8	86.5%	19.8	86.7%	19.7			
HK6023TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8	86.5%	19.8	86.7%	19.7			
HK6023TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	85.6%	20.0	85.8%	19.9	86.0%	19.9	86.2%	19.8	86.5%	19.8	86.7%	19.7			
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											4.9%	4.7%	4.4%	4.2%	3.9%	3.7%						

ネボン株式会社

【ハウスナキ 25、25E型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																	
				(kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005	
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)
25型 ・ 25E型	1997 (H9)	2005 (H17)	HK1525SC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.9%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.0%	5.0	86.2%	5.0	86.5%	5.0	86.7%	5.0
			HK1525SE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.9%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.0%	5.0	86.2%	5.0	86.5%	5.0	86.7%	5.0
			HK1525TC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.9%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.0%	5.0	86.2%	5.0	86.5%	5.0	86.7%	5.0
			HK1525TE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.9%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.0%	5.0	86.2%	5.0	86.5%	5.0	86.7%	5.0
			HK1525TOP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		84.9%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.0%	5.0	86.2%	5.0	86.5%	5.0	86.7%	5.0
			HK1525TEP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95	静音形	84.9%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.0%	5.0	86.2%	5.0	86.5%	5.0	86.7%	5.0
			HK1525TEP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95	静音形	84.9%	5.1	85.2%	5.1	85.4%	5.1	85.6%	5.1	85.8%	5.0	86.0%	5.0	86.2%	5.0	86.5%	5.0	86.7%	5.0
			HK2025SC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025SE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025SR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025TR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	スイング形	84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025TCS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形	84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025TES	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形	84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK2025TRS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6	静音形	84.9%	6.7	85.2%	6.7	85.4%	6.7	85.6%	6.7	85.8%	6.6	86.0%	6.6	86.2%	6.6	86.5%	6.6	86.7%	6.6
			HK3025SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025SR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TCE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TEE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK3025TFE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		84.9%	10.1	85.2%	10.0	85.4%	10.0	85.6%	10.0	85.8%	10.0	86.0%	9.9	86.2%	9.9	86.5%	9.9	86.7%	9.9
			HK4025TC	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TE	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TF	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形 50Hz	84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形 60Hz	84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TCE	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TEE	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK4025TFE	100,000	116	13.0	88.0%	A重油	9.9~13.2		84.9%	13.4	85.2%	13.4	85.4%	13.4	85.6%	13.3	85.8%	13.3	86.0%	13.3	86.2%	13.2	86.5%	13.2	86.7%	13.2
			HK5025TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5025TE	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5025TF	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5025TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5025TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5025TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
			HK5025TCE	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4
HK5025TEE	125,000	145	16.2	88.0%	A重油	13.2~16.5		84.9%	16.8	85.2%	16.7	85.4%	16.7	85.6%	16.6	85.8%	16.6	86.0%	16.6	86.2%	16.5	86.5%	16.5	86.7%	16.4			
HK5025TFE	125,0																											

ネボン株式会社  
【ハウスホウキ 25Z型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																			
				kcal/h)	(kW)						1997		1998		1999		2000		2001		2002		2003		2004		2005			
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)		
25Z型	1997 (H9)	2005 (H17)	HK3025SCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6	
			HK3025SEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6	
			HK3025SRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK3025TCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK3025TEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK3025TFZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK3025TRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK3025TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK3025TESZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK3025TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形			86.9%	9.8	87.2%	9.8	87.4%	9.8	87.6%	9.8	87.8%	9.7	88.0%	9.7	88.2%	9.7	88.5%	9.7	88.7%	9.6
			HK4025TCZ	100,000	116	12.7	90.0%	A重油	9.9~13.2				86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TEZ	100,000	116	12.7	90.0%	A重油	9.9~13.2				86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TFZ	100,000	116	12.7	90.0%	A重油	9.9~13.2				86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TR5Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TR6Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TCSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TESZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TFSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK4025TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形			86.9%	13.1	87.2%	13.1	87.4%	13.0	87.6%	13.0	87.8%	13.0	88.0%	13.0	88.2%	12.9	88.5%	12.9	88.7%	12.9
			HK5025TCZ	125,000	145	15.8	90.0%	A重油	13.2~16.5				86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1	88.5%	16.1	88.7%	16.1
			HK5025TEZ	125,000	145	15.8	90.0%	A重油	13.2~16.5				86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1	88.5%	16.1	88.7%	16.1
			HK5025TFZ	125,000	145	15.8	90.0%	A重油	13.2~16.5				86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1	88.5%	16.1	88.7%	16.1
			HK5025TCSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1	88.5%	16.1	88.7%	16.1
			HK5025TESZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1	88.5%	16.1	88.7%	16.1
			HK5025TFSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形			86.9%	16.4	87.2%	16.4	87.4%	16.3	87.6%	16.3	87.8%	16.2	88.0%	16.2	88.2%	16.1	88.5%	16.1	88.7%	16.1
			HK6025TCZ	150,000	174	19.0	90.0%	A重油	16.5~19.8				86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4	88.5%	19.3	88.7%	19.3
			HK6025TEZ	150,000	174	19.0	90.0%	A重油	16.5~19.8				86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4	88.5%	19.3	88.7%	19.3
			HK6025TFZ	150,000	174	19.0	90.0%	A重油	16.5~19.8				86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4	88.5%	19.3	88.7%	19.3
HK6025TCSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4	88.5%	19.3	88.7%	19.3			
HK6025TESZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4	88.5%	19.3	88.7%	19.3			
HK6025TFSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形			86.9%	19.7	87.2%	19.6	87.4%	19.6	87.6%	19.5	87.8%	19.5	88.0%	19.4	88.2%	19.4	88.5%	19.3	88.7%	19.3			
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											3.4%	3.2%	2.9%	2.7%	2.4%	2.2%	1.9%	1.7%	1.5%											



ネボン株式会社  
【ハウスカオンキ 24型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
24型	2005 (H17)	2007 (H19)	HK3024TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3024TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3024TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3024TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	スイング形	86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3024TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3024TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3024TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9	静音形	86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK4024TC	100,000	116	13.0	88.0%	A重油	9.9~13.2		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TE	100,000	116	13.0	88.0%	A重油	9.9~13.2		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TF	100,000	116	13.0	88.0%	A重油	9.9~13.2		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 50Hz	86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2	スイング形, 60Hz	86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TES	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4024TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2	静音形	86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK5024TC	125,000	145	16.2	88.0%	A重油	13.2~16.5		86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5024TE	125,000	145	16.2	88.0%	A重油	13.2~16.5		86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5024TF	125,000	145	16.2	88.0%	A重油	13.2~16.5		86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5024TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5024TES	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5024TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5	静音形	86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK6024TC	150,000	174	19.4	88.0%	A重油	16.5~19.8		86.7%	19.7	86.9%	19.7	87.1%	19.6
			HK6024TE	150,000	174	19.4	88.0%	A重油	16.5~19.8		86.7%	19.7	86.9%	19.7	87.1%	19.6
HK6024TF	150,000	174	19.4	88.0%	A重油	16.5~19.8		86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6024TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6024TES	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6024TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8	静音形	86.7%	19.7	86.9%	19.7	87.1%	19.6			
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算										3.7%		3.4%		3.2%		

ネボン株式会社

【ハウスカオキ 24Z型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
											%	(l/h)	%	(l/h)	%	(l/h)
24Z型	2005 (H17)	2007 (H19)	HK3024TCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3024TEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3024TFZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3024TRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3024TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3024TESZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3024TFSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK4024TCZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TEZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TFZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TR6Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TCSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TESZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TFSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4024TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK5024TCZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5024TEZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5024TFZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5024TCSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5024TESZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5024TFSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK6024TCZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.7%	19.3	88.9%	19.2	89.1%	19.2
			HK6024TEZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.7%	19.3	88.9%	19.2	89.1%	19.2
HK6024TFZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6024TCSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6024TESZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6024TFSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	88.7%	19.3	88.9%	19.2	89.1%	19.2			
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											1.5%		1.2%		1.0%	

ネポ ン 株式会社

【ハウスコンキ 24V型シリーズ】

2011 年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)					2007		2008			
										%	(l/h)	%	(l/h)		
24V型	2007 (H19)	現行	HK3024TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	89.1%	9.6	89.3%	9.6		
			HK3024TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	89.1%	9.6	89.3%	9.6		
			HK4024TCV	100,000	116	12.7	90.0%	A重油	9.9~13.2	89.1%	12.8	89.3%	12.8		
			HK4024TEV	100,000	116	12.7	90.0%	A重油	9.9~13.2	89.1%	12.8	89.3%	12.8		
			HK5024TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5	89.1%	16.0	89.3%	15.9		
			HK5024TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5	89.1%	16.0	89.3%	15.9		
			HK5024TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5	89.1%	16.0	89.3%	15.9		
			HK6024TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8	89.1%	19.2	89.3%	19.1		
			HK6024TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8	89.1%	19.2	89.3%	19.1		
			HK6024TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8	89.1%	19.2	89.3%	19.1		
現行機種（機器熱効率 90%）へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算									1.0%	0.7%					

ネポン株式会社  
【ハウスコンキ 27型シリーズ】

2011年度 (平成 23 年度) 熱効率率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量							
				(kcal/h)	(kW)						2005		2006		2007			
											%	(l/h)	%	(l/h)	%	(l/h)		
27型	2005 (H17)	2007 (H19)	HK1527SC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527SE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527TC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527TE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527TCP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		静音形		86.7%	5.0	86.9%	5.0	87.1%	5.0
			HK1527TEP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		静音形		86.7%	5.0	86.9%	5.0	87.1%	5.0
			HK2027SC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027SE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027SR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		スイング形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TCS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		静音形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TES	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		静音形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TRS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		静音形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK3027SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027SR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		スイング形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		スイング形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK4027TC	100,000	116	13.0	88.0%	A重油	9.9~13.2				86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TE	100,000	116	13.0	88.0%	A重油	9.9~13.2				86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TF	100,000	116	13.0	88.0%	A重油	9.9~13.2				86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2		スイング形, 50Hz		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2		スイング形, 60Hz		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TES	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK5027TC	125,000	145	16.2	88.0%	A重油	13.2~16.5				86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TE	125,000	145	16.2	88.0%	A重油	13.2~16.5				86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TF	125,000	145	16.2	88.0%	A重油	13.2~16.5				86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TR	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形		86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TCS </td <td>125,000</td> <td>145</td> <td>16.2</td> <td>88.0%</td> <td>A重油</td> <td>13.2~16.5</td> <td></td> <td>静音形</td> <td></td> <td>86.7%</td> <td>16.4</td> <td>86.9%</td> <td>16.4</td> <td>87.1%</td> <td>16.4</td>	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形		86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TES	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形		86.7%	16.4	86.9%	16.4	87.1%	16.4
HK5027TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形		86.7%	16.4	86.9%	16.4	87.1%	16.4			
HK6027TC	150,000	174	19.4	88.0%	A重油	16.5~19.8				86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TE	150,000	174	19.4	88.0%	A重油	16.5~19.8				86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TF	150,000	174	19.4	88.0%	A重油	16.5~19.8				86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TR	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形		86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TES	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形		86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形		86.7%	19.7	86.9%	19.7	87.1%	19.6			
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											3.7%		3.4%		3.2%			

ネポ`ン株式会社

【ハウスカンキ 27Z型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覽表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量					
				(kcal/h)	(kW)						2005		2006		2007	
						%	(l/h)	%	(l/h)	%	(l/h)					
27Z型	2005 (H17)	2007 (H19)	HK1527TCZ	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		88.7%	4.9	88.9%	4.9	89.1%	4.9
			HK1527TEZ	38,000	44.2	4.8	90.0%	A重油	3.3~4.95		88.7%	4.9	88.9%	4.9	89.1%	4.9
			HK2027TCZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6		88.7%	6.4	88.9%	6.4	89.1%	6.4
			HK2027TEZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6		88.7%	6.4	88.9%	6.4	89.1%	6.4
			HK2027TRZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	スイング形	88.7%	6.4	88.9%	6.4	89.1%	6.4
			HK2027TCSZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	静音形	88.7%	6.4	88.9%	6.4	89.1%	6.4
			HK2027TESZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	静音形	88.7%	6.4	88.9%	6.4	89.1%	6.4
			HK2027TRSZ	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	静音形	88.7%	6.4	88.9%	6.4	89.1%	6.4
			HK3027TCZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3027TEZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3027TFZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9		88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3027TRZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3027TCSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3027TESZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK3027TRSZ	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	静音形	88.7%	9.6	88.9%	9.6	89.1%	9.6
			HK4027TCZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TEZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TFZ	100,000	116	12.7	90.0%	A重油	9.9~13.2		88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TR5Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TR6Z	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TCSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TESZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TFSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK4027TRSZ	100,000	116	12.7	90.0%	A重油	9.9~13.2	静音形	88.7%	12.9	88.9%	12.8	89.1%	12.8
			HK5027TCZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5027TEZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5027TFZ	125,000	145	15.8	90.0%	A重油	13.2~16.5		88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5027TCSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5027TESZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	88.7%	16.1	88.9%	16.0	89.1%	16.0
			HK5027TFSZ	125,000	145	15.8	90.0%	A重油	13.2~16.5	静音形	88.7%	16.1	88.9%	16.0	89.1%	16.0
HK6027TCZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6027TEZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6027TFZ	150,000	174	19.0	90.0%	A重油	16.5~19.8		88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6027TCSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6027TESZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	88.7%	19.3	88.9%	19.2	89.1%	19.2			
HK6027TFSZ	150,000	174	19.0	90.0%	A重油	16.5~19.8	静音形	88.7%	19.3	88.9%	19.2	89.1%	19.2			
現行機種 (機器熱効率 90% )へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算										1.5%	1.2%	1.0%				

ネボン株式会社

【ハウスカオンキ 27V型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量								
				(kcal/h)	(kW)						2007		2008						
											%	(l/h)	%	(l/h)					
27V型	2007 (H19)	現行	HK1527TCV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95			89.1%	4.9	89.3%	4.8				
			HK1527TEV	38,000	44.2	4.8	90.0%	A重油	3.3~4.95				89.1%	4.9	89.3%	4.8			
			HK2027TCV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6				89.1%	6.4	89.3%	6.4			
			HK2027TEV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6				89.1%	6.4	89.3%	6.4			
			HK2027TRV	50,000	58.1	6.4	90.0%	A重油	4.95~6.6	スイング形			89.1%	6.4	89.3%	6.4			
			HK3027TCV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				89.1%	9.6	89.3%	9.6			
			HK3027TEV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				89.1%	9.6	89.3%	9.6			
			HK3027TFV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9				89.1%	9.6	89.3%	9.6			
			HK3027TRV	75,000	87.2	9.5	90.0%	A重油	6.6~9.9	スイング形			89.1%	9.6	89.3%	9.6			
			HK4027TCV	100,000	116	12.7	90.0%	A重油	9.9~13.2				89.1%	12.8	89.3%	12.8			
			HK4027TEV	100,000	116	12.7	90.0%	A重油	9.9~13.2				89.1%	12.8	89.3%	12.8			
			HK4027TFV	100,000	116	12.7	90.0%	A重油	9.9~13.2				89.1%	12.8	89.3%	12.8			
			HK4027FRV	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 50Hz			89.1%	12.8	89.3%	12.8			
			HK4027GRV	100,000	116	12.7	90.0%	A重油	9.9~13.2	スイング形, 60Hz			89.1%	12.8	89.3%	12.8			
			HK4027TYV	100,000	116	12.7	90.0%	A重油	9.9~13.2	低床スイング形			89.1%	12.8	89.3%	12.8			
			HK5027TCV	125,000	145	15.8	90.0%	A重油	13.2~16.5				89.1%	16.0	89.3%	15.9			
			HK5027TEV	125,000	145	15.8	90.0%	A重油	13.2~16.5				89.1%	16.0	89.3%	15.9			
			HK5027TFV	125,000	145	15.8	90.0%	A重油	13.2~16.5				89.1%	16.0	89.3%	15.9			
HK6027TCV	150,000	174	19.0	90.0%	A重油	16.5~19.8				89.1%	19.2	89.3%	19.1						
HK6027TEV	150,000	174	19.0	90.0%	A重油	16.5~19.8				89.1%	19.2	89.3%	19.1						
HK6027TFV	150,000	174	19.0	90.0%	A重油	16.5~19.8				89.1%	19.2	89.3%	19.1						
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											1.0%	0.7%							