

ネボン株式会社

【ハウスナキ 8、10型シリーズ】

2011年度 (平成 23 年度) 熱効率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量																		
				(kcal/h)	(kW)						1983		1984		1985		1986		1987		1988								
											%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)	%	(l/h)							
8型	1983 (S58)	1985 (S60)	HK158SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			81.9%	4.5	82.1%	4.4	82.3%	4.4												
			HK158TE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95			81.9%	4.5	82.1%	4.4	82.3%	4.4												
			HK208TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			81.9%	7.0	82.1%	6.9	82.3%	6.9												
			HK208TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6			81.9%	7.0	82.1%	6.9	82.3%	6.9												
			HK308SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK308SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK308TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK308TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK318TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9			81.9%	10.4	82.1%	10.4	82.3%	10.4												
			HK408TE	87,000	101	11.3	88.0%	A重油	9.9~13.2			81.9%	12.1	82.1%	12.1	82.3%	12.1												
			HK408TC	87,000	101	11.3	88.0%	A重油	9.9~13.2			81.9%	12.1	82.1%	12.1	82.3%	12.1												
			HK418TC	87,000	101	11.3	88.0%	A重油	9.9~13.2			81.9%	12.1	82.1%	12.1	82.3%	12.1												
			HK508TC	125,000	145	16.2	88.0%	A重油	13.2~16.5			81.9%	17.4	82.1%	17.4	82.3%	17.3												
			HK608TC	150,000	174	19.4	88.0%	A重油	16.5~19.8			81.9%	20.9	82.1%	20.8	82.3%	20.8												
			10型	1985 (S60)	1988 (S63)	HK160SE	32,000	37.2	4.2	88.0%	A重油	3.3~4.95						82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4				
HK160SC	32,000	37.2				4.2	88.0%	A重油	3.3~4.95							82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TE	32,000	37.2				4.2	88.0%	A重油	3.3~4.95							82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TC	32,000	37.2				4.2	88.0%	A重油	3.3~4.95							82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TEP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95		静音形					82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK160TCP	32,000	37.2				4.2	88.0%	A重油	3.3~4.95		静音形					82.3%	4.4	82.5%	4.4	82.7%	4.4	83.0%	4.4						
HK210SE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210SC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TE	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TC	50,000	58.1				6.5	88.0%	A重油	4.95~6.6							82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TEP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6		静音形					82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK210TCP	50,000	58.1				6.5	88.0%	A重油	4.95~6.6		静音形					82.3%	6.9	82.5%	6.9	82.7%	6.9	83.0%	6.9						
HK310SE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310SC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TE	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TC	75,000	87.2				9.7	88.0%	A重油	6.6~9.9							82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TEP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		静音形					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TCP	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		静音形					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TCM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムナ					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TEM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムナ					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK310TFM	75,000	87.2				9.7	88.0%	A重油	6.6~9.9		システムナ					82.3%	10.4	82.5%	10.4	82.7%	10.3	83.0%	10.3						
HK410TE	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TC	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TEP	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TCP	87,000	101				11.3	88.0%	A重油	9.9~13.2							82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TCM	87,000	101				11.3	88.0%	A重油	9.9~13.2		システムナ					82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TEM	87,000	101				11.3	88.0%	A重油	9.9~13.2		システムナ					82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK410TFM	87,000	101				11.3	88.0%	A重油	9.9~13.2		システムナ					82.3%	12.1	82.5%	12.0	82.7%	12.0	83.0%	12.0						
HK510TC	125,000	145				16.2	88.0%	A重油	13.2~16.5							82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2						
HK510TEP	125,000	145				16.2	88.0%	A重油	13.2~16.5		静音形					82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2						
HK510TCM	125,000	145	16.2	88.0%	A重油	13.2~16.5		システムナ					82.3%	17.3	82.5%	17.3	82.7%	17.2	83.0%	17.2									
HK610TC	150,000	174	19.4	88.0%	A重油	16.5~19.8							82.3%	20.8	82.5%	20.7	82.7%	20.7	83.0%	20.6									
HK610TEP	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形					82.3%	20.8	82.5%	20.7	82.7%	20.7	83.0%	20.6									
HK610TCM	150,000	174	19.4	88.0%	A重油	16.5~19.8		システムナ					82.3%	20.8	82.5%	20.7	82.7%	20.7	83.0%	20.6									
HK810TC	200,000	233	25.9	88.0%	A重油	19.8~26.4							82.3%	27.7	82.5%	27.6	82.7%	27.6	83.0%	27.5									
現行機種 (機器熱効率 90%) へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											9.0%	8.8%	8.6%	8.3%	8.1%	7.8%													