

ネポﾝ株式会社
【ハウスカウキ 27型シリーズ】

2011年度 (平成 23 年度) 熱効率率/燃料消費量 経年変化一覧表

製品 シリーズ	製造 開始年	製造 終了年	製品型式	熱出力		燃料 消費量 (l/h)	熱効率	燃料	標準暖房 面積 (a)	備考	製造年度別 経年変化による現在の熱効率および燃料消費量							
				(kcal/h)	(kW)						2005		2006		2007			
											%	(l/h)	%	(l/h)	%	(l/h)		
27型	2005 (H17)	2007 (H19)	HK1527SC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527SE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527TC	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527TE	38,000	44.2	4.9	88.0%	A重油	3.3~4.95			86.7%	5.0	86.9%	5.0	87.1%	5.0	
			HK1527TCP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		静音形		86.7%	5.0	86.9%	5.0	87.1%	5.0
			HK1527TEP	38,000	44.2	4.9	88.0%	A重油	3.3~4.95		静音形		86.7%	5.0	86.9%	5.0	87.1%	5.0
			HK2027SC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027SE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027SR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TC	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TE	50,000	58.1	6.5	88.0%	A重油	4.95~6.6				86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TR	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		スイング形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TCS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		静音形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TES	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		静音形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK2027TRS	50,000	58.1	6.5	88.0%	A重油	4.95~6.6		静音形		86.7%	6.6	86.9%	6.6	87.1%	6.5
			HK3027SC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027SE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027SR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		スイング形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TC	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TE	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TF	75,000	87.2	9.7	88.0%	A重油	6.6~9.9				86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TR	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		スイング形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TCS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TES	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK3027TFS	75,000	87.2	9.7	88.0%	A重油	6.6~9.9		静音形		86.7%	9.9	86.9%	9.8	87.1%	9.8
			HK4027TC	100,000	116	13.0	88.0%	A重油	9.9~13.2				86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TE	100,000	116	13.0	88.0%	A重油	9.9~13.2				86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TF	100,000	116	13.0	88.0%	A重油	9.9~13.2				86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TR5	100,000	116	13.0	88.0%	A重油	9.9~13.2		スイング形, 50Hz		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TR6	100,000	116	13.0	88.0%	A重油	9.9~13.2		スイング形, 60Hz		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TCS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TES	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TFS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK4027TRS	100,000	116	13.0	88.0%	A重油	9.9~13.2		静音形		86.7%	13.2	86.9%	13.1	87.1%	13.1
			HK5027TC	125,000	145	16.2	88.0%	A重油	13.2~16.5				86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TE	125,000	145	16.2	88.0%	A重油	13.2~16.5				86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TF	125,000	145	16.2	88.0%	A重油	13.2~16.5				86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TCS	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形		86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TES	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形		86.7%	16.4	86.9%	16.4	87.1%	16.4
			HK5027TFS	125,000	145	16.2	88.0%	A重油	13.2~16.5		静音形		86.7%	16.4	86.9%	16.4	87.1%	16.4
HK6027TC	150,000	174	19.4	88.0%	A重油	16.5~19.8				86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TE	150,000	174	19.4	88.0%	A重油	16.5~19.8				86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TF	150,000	174	19.4	88.0%	A重油	16.5~19.8				86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TCS	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形		86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TES	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形		86.7%	19.7	86.9%	19.7	87.1%	19.6			
HK6027TFS	150,000	174	19.4	88.0%	A重油	16.5~19.8		静音形		86.7%	19.7	86.9%	19.7	87.1%	19.6			
現行機種 (機器熱効率 90%)へ設備更新した場合の 経年変化分 燃料消費節減率 ※同等熱出力換算											3.7%		3.4%		3.2%			